


BWA QLV Bewehrungsanschluss quer und längs verzahnt


- Zweireihig / Standardbügelform = Typ „B“ / Elementlänge 125 cm



Bestell-Nr.	Bezeichnung	Stahl „ds“ Ø mm	Bügel			„lü“ mm	Box			Palette m
			Bügelabstand „s“ in mm	Höhe „h“ in mm	Bügel „b“ in mm		Breite „B“ in mm	Höhe „H1“ in mm	Höhe „H2“ mit Deckel mm	
BWA 120										
1200815V	BWA 120-08/15V	8	150	170	88	320	118	12	45	150
1200820V	BWA 120-08/20V	8	200	170	88	320	118	12	45	150
1200825V	BWA 120-08/25V	8	250	170	88	320	118	12	45	150
BWA 150										
1500815V	BWA 150-08/15V	8	150	170	116	320	148	12	45	150
1500820V	BWA 150-08/20V	8	200	170	116	320	148	12	45	150
1500825V	BWA 150-08/25V	8	250	170	116	320	148	12	45	150
1501010V	BWA 150-10/10V	10	100	170	118	360	148	12	45	150
1501015V	BWA 150-10/15V	10	150	170	118	390	148	12	45	150
1501020V	BWA 150-10/20V	10	200	170	118	390	148	12	45	150
1501025V	BWA 150-10/25V	10	250	170	118	390	148	12	45	150
1501210V	BWA 150-12/10V	12	100	170	120	310	148	12	45	125
1501215V	BWA 150-12/15V	12	150	170	120	460	148	12	45	125
1501220V	BWA 150-12/20V	12	200	170	120	460	148	12	45	125
1501225V	BWA 150-12/25V	12	250	170	120	460	148	12	45	125
BWA 190										
1900815V	BWA 190-08/15V	8	150	170	152	320	188	12	45	125
1900820V	BWA 190-08/20V	8	200	170	152	320	188	12	45	125
1900825V	BWA 190-08/25V	8	250	170	152	320	188	12	45	125
1901015V	BWA 190-10/15V	10	150	170	154	390	188	12	45	125
1901020V	BWA 190-10/20V	10	200	170	154	390	188	12	45	125
1901025V	BWA 190-10/25V	10	250	170	154	390	188	12	45	125
1901210V	BWA 190-12/10V	12	100	170	156	430	188	12	45	125
1901215V	BWA 190-12/15V	12	150	170	156	460	188	12	45	125
1901220V	BWA 190-12/20V	12	200	170	156	460	188	12	45	125
1901225V	BWA 190-12/25V	12	250	170	156	460	188	12	45	125

BWA QLV Bewehrungsanschluss quer und längs verzahnt

- Zweireihig / Standardbügelform = Typ „B“ / Elementlänge 125 cm



Bestell-Nr.	Bezeichnung	Stahl „ds“ Ø mm	Bügel			„lü“ mm	Box			Palette m
			Bügelabstand „s“ in mm	Höhe „h“ in mm	Bügel „b“ in mm		Breite „B“ in mm	Höhe „H1“ in mm	Höhe „H2“ mit Deckel mm	
BWA 220										
2200815V	BWA 220-08/15V	8	150	170	188	320	218	12	45	80
2200820V	BWA 220-08/20V	8	200	170	188	320	218	12	45	80
2200825V	BWA 220-08/25V	8	250	170	188	320	218	12	45	80
2201010V	BWA 220-10/10V	10	100	170	190	390	218	12	45	80
2201015V	BWA 220-10/15V	10	150	170	190	390	218	12	45	80
2201020V	BWA 220-10/20V	10	200	170	190	390	218	12	45	80
2201025V	BWA 220-10/25V	10	250	170	190	390	218	12	45	80
2201210V	BWA 220-12/10V	12	100	170	192	460	218	12	45	80
2201215V	BWA 220-12/15V	12	150	170	192	460	218	12	45	80
2201220V	BWA 220-12/20V	12	200	170	192	460	218	12	45	80
2201225V	BWA 220-12/25V	12	250	170	192	460	218	12	45	80