


### VB Quadropod – with plastic feet

- Stable support for the top layer of the reinforcement.
- Ideally suited for ceilings / floorings with integrated heating or cooling systems.
- Includes push-on feet.
- Rust protection through plug-on plastic caps with a contact face of 14 mm, 45 mm, or poured concrete feet.
- Large plastic feet for soft subsoil. Poured concrete feet for fair-faced concrete.



plastic foot F 14 mm  
VB standard: X = without  
with crossbar QT: X = 5



plastic foot GF 45 mm  
VB with GF: X = 6  
with crossbar QT: X = 7



poured concrete foot  
VB with BF: X = 8  
with crossbar QT: X = 9

| article no. | designation | range Ø (cm) | height (cm) | steel Ø (mm) | pcs. / pack |
|-------------|-------------|--------------|-------------|--------------|-------------|
| 946X056     | VB 05 / 6   | 30           | 5           | 6            | 50          |
| 946X066     | VB 06 / 6   | 30           | 6           | 6            | 50          |
| 946X076     | VB 07 / 6   | 30           | 7           | 6            | 50          |
| 946X086     | VB 08 / 6   | 30           | 8           | 6            | 50          |
| 946X096     | VB 09 / 6   | 30           | 9           | 6            | 50          |
| 946X106     | VB 10 / 6   | 30           | 10          | 6            | 50          |
| 946X116     | VB 11 / 6   | 30           | 11          | 6            | 50          |
| 946X126     | VB 12 / 6   | 30           | 12          | 6            | 50          |
| 946X136     | VB 13 / 6   | 30           | 13          | 6            | 50          |
| 946X146     | VB 14 / 6   | 30           | 14          | 6            | 50          |
| 946X156     | VB 15 / 6   | 30           | 15          | 6            | 50          |
| 946X166     | VB 16 / 6   | 30           | 16          | 6            | 50          |
| 946X176     | VB 17 / 6   | 30           | 17          | 6            | 50          |
| 946X186     | VB 18 / 6   | 30           | 18          | 6            | 50          |
| 946X196     | VB 19 / 6   | 30           | 19          | 6            | 50          |
| 946X206     | VB 20 / 6   | 30           | 20          | 6            | 50          |
| 946X216     | VB 21 / 6   | 30           | 21          | 6            | 50          |
| 946X226     | VB 22 / 6   | 30           | 22          | 6            | 50          |
| 946X236     | VB 23 / 6   | 30           | 23          | 6            | 50          |
| 946X246     | VB 24 / 6   | 30           | 24          | 6            | 50          |
| 946X256     | VB 25 / 6   | 30           | 25          | 6            | 50          |
| 946X266     | VB 26 / 6   | 30           | 26          | 6            | 50          |
| 946X276     | VB 27 / 6   | 30           | 27          | 6            | 50          |
| 946X286     | VB 28 / 6   | 30           | 28          | 6            | 50          |
| 946X296     | VB 29 / 6   | 30           | 29          | 6            | 50          |
| 946X306     | VB 30 / 6   | 30           | 30          | 6            | 50          |

Approved according to DBV-specification "Unterstützungen nach Eurocode 2".

