

SB Hexapod – with plastic feet

- Extremely stable support for the top layer of the reinforcement.
- Very high stability through multiple overlapping and welded reinforcing brackets.
- Ideally suited for ceilings / floorings with integrated heating or cooling systems.
- Includes push-on feet.
- Rust protection through plug-on plastic caps with a contact face of 14 mm, 45 mm, or poured concrete feet.
- Large plastic feet for soft subsoil. Poured concrete feet for fair-faced concrete.

article no.	designation	range Ø (cm)	height (cm)	steel Ø (mm)	pcs. / pack
947X056	SB 05 / 6	41	5	6	50
947X066	SB 06 / 6	41	6	6	50
947X076	SB 07 / 6	41	7	6	50
947X086	SB 08 / 6	41	8	6	50
947X096	SB 09 / 6	41	9	6	50
947X106	SB 10 / 6	41	10	6	50
947X116	SB 11 / 6	41	11	6	50
947X126	SB 12 / 6	41	12	6	50
947X136	SB 13 / 6	41	13	6	50
947X146	SB 14 / 6	41	14	6	50
947X156	SB 15 / 6	41	15	6	50
947X166	SB 16 / 6	41	16	6	50
947X176	SB 17 / 6	41	17	6	50
947X186	SB 18 / 6	41	18	6	50
947X196	SB 19 / 6	41	19	6	50
947X206	SB 20 / 6	41	20	6	50
947X216	SB 21 / 6	41	21	6	50
947X226	SB 22 / 6	41	22	6	50
947X236	SB 23 / 6	41	23	6	50
947X246	SB 24 / 6	41	24	6	50
947X256	SB 25 / 6	41	25	6	50
947X266	SB 26 / 6	41	26	6	50
947X276	SB 27 / 6	41	27	6	50
947X286	SB 28 / 6	41	28	6	50
947X296	SB 29 / 6	41	29	6	50
947X306	SB 30 / 6	41	30	6	50

Approved according to DBV-specification "Unterstützungen nach Eurocode 2".



plastic foot F 14 mm
VB standard: X = without
with crossbar QT: X = 5



plastic foot GF 45 mm
VB with GF: X = 6
with crossbar QT: X = 7



poured concrete foot
VB with BF: X = 8
with crossbar QT: X = 9

