



article no.:

X = 08: steel Ø 8 mm

X = 10: steel Ø 10 mm

example:

3208200 = DWA S 200-08

wall thickness 200mm,  
steel Ø 08mm

## DWA S Double-wall spacer "Shoe"

- For the production of precast double walls.
- Concrete cover from 15 mm to 35 mm.

article no.	designation	wall thickness (mm)	steel Ø (mm)	units / sac	units / pallet
32X120	DWA S 120 - X	120	X	100	3.000
32X140	DWA S 140 - X	140	X	100	3.000
32X150	DWA S 150 - X	150	X	100	3.000
32X160	DWA S 160 - X	160	X	100	3.000
32X180	DWA S 180 - X	180	X	100	3.000
32X200	DWA S 200 - X	200	X	100	3.000
32X240	DWA S 240 - X	240	X	100	3.000
32X250	DWA S 250 - X	250	X	100	3.000
32X300	DWA S 300 - X	300	X	50	3.000
32X350	DWA S 350 - X	350	X	50	2.000
32X360	DWA S 360 - X	360	X	50	2.000
32X365	DWA S 365 - X	365	X	50	2.000
32X400	DWA S 400 - X	400	X	50	2.000
32X500	DWA S 500 - X	500	X	50	2.000

Approved according to DBV-specification "Abstandhalter" DBV -c- L1/T/A.



steel Ø 8 mm



foot for steel Ø 10 mm

## DWA K Double-wall spacer "Four-way foot"

- For the production of precast double walls.
- Concrete cover from 20 mm to 35 mm.
- DWA K with 10 mm Steel has a lowered foot and is non-penetrable.
- In case of steel diameter 10 mm: material ABS.
- Same wall thicknesses available as for DWA S.

article no.	designation	wall thickness (mm)	steel Ø (mm)	units / sac	units / pallet
32908200	DWA K 200 - 08	200	8	100	3.000
32908240	DWA K 240 - 08	240	8	100	3.000
32908250	DWA K 250 - 08	250	8	100	3.000
32908300	DWA K 300 - 08	300	8	50	2.000
32908360	DWA K 360 - 08	360	8	50	2.000
32908400	DWA K 400 - 08	400	8	50	2.000
32910200	DWA K 200 - 10	200	10	100	3.000
32910240	DWA K 240 - 10	240	10	100	3.000
32910250	DWA K 250 - 10	250	10	100	3.000
32910300	DWA K 300 - 10	300	10	50	2.000
32910360	DWA K 360 - 10	360	10	50	2.000
32910400	DWA K 400 - 10	400	10	50	2.000

Other lengths and wall thicknesses upon request.

Approved according to DBV-specification "Abstandhalter" DBV -c- L1/T/A.