


RAS RF Ring-shaped spacer round feet



- Large-area spacer for the bottom layer of the reinforcement, consisting of six nested rings of a diameter from 19 cm to 31 cm.

article no.	designation	concrete cover (mm)	pcs / sac	pcs / pallet
3915	RAS 15 RF	15	300	12.000
3920	RAS 20 RF	20	300	12.000
3925	RAS 25 RF	25	300	12.000
3930	RAS 30 RF	30	300	9.600
3935	RAS 35 RF	35	300	9.000

Approved according to DBV-specification "Abstandhalter" DBV -c- F/T/A.




RAS RF V Ring-shaped spacer round feet – reinforced



- Reinforced large-area spacer for the bottom layer of the reinforcement, consisting of five nested rings of a diameter from 19 cm to 38 cm.

article no.	designation	concrete cover (mm)	pcs / sac	pcs / pallet
3921	RAS 20 V RF	20	150	5.400
3926	RAS 25 V RF	25	150	5.400
3931	RAS 30 V RF	30	150	4.650
3936	RAS 35 V RF	35	100	3.600
3941	RAS 40 V RF	40	100	3.000
3951	RAS 50 V RF	50	100	2.700

Approved according to DBV-specification "Abstandhalter" DBV -c- F/T/A.



RAS EV Ring-shaped spacer – extra reinforced



- Stable large-area spacer for the bottom layer of the reinforcement, consisting of five nested rings of a diameter of 19 cm to 33 cm.

article no.	designation	concrete cover (mm)	pcs / sac	pcs / pallet
3914	RAS 20 EV	20	125	4.500
3918	RAS 25 EV	25	125	4.500
3922	RAS 30 EV	30	125	4.500
3924	RAS 35 EV	35	100	4.500
3928	RAS 40 EV	40	100	4.500
3932	RAS 50 EV	50	100	4.500